## **KEY**

## **ATTRIBUTES**



Approx roll length of material in linear metres (m) & feet (ft)



Approx width of material in centimetres (cm) & inches (")



Approx weight in grams per metre squared (g/m²)



Approx thickness in (mm)

## **CUSTOM DYE INFO**



Ability to custom dve



Order lead time



Minimum order quantity

## **TECHNICAL**



NDFR

Non Durably Flame Retardant chemically treated with a water solution and if wetted in any way should be retreated



DFR

**Durably Flame Retardant** chemically treated to withstand a number of cleanings



IFR

Inherently Flame Retardant woven from fibres with a high flame retardancy



FR

Flame Retardant chemically treated to an individual specification



NOT FR

Not Flame Retardant no flame retardant treatment



Recyclable



Confirmation that the fabric meets one or more flame retardant standards

**BS5867** BS5867 Pt2 B is the British Standard for flame retardant fabrics used for curtains and drapes

**BS5852** BS5852 Pt1 is the British Standard for flammability of upholstered composites for seating

**BS4790** BS4790: 1987 Determination of the effects of a small source of ignition on textile floor coverings hot metal nut method (method 1, loose laid)

**EN13773: 2003** Meets European fire safety standards for vertically hung fabrics. Burning behavior, ignitability testing of curtain fabric for use in the contract market.

TL 1080-0002/8 German Military Specification for horizontally tested materials

**EN14041** Details the requirement for CE Marking of textiles, laminate and resilient floor coverings

BS7905-1:2001 Lifting equipment for performance, broadcast and similar applications.

M1. M2. M4 Conforms to French Fire Regulations

B1, B2 Conforms to German Fire Regulations DIN 4102

**IMO** Conforms to International Maritime Organisation regulations

Classe Uno Meets Italian Fire Regulations

**BS EN13501-1** Fire Classification of construction, products and building elements. Classification using test data from reaction to fire tests

CFC EN ISO 9239-1 Reaction to fire test. Horizontal surface spread of flame on floor covering system. Determination of the burning behaviour using a retardant heat source

NFPA 701 NFPA 701: (USA) Standard Methods of Fire Tests for Flame Propagation of Textiles and Films

**EN9239-1** Reaction to fire tests – horizontal surface spread of flame on floor covering systems

**DIN EN1021** Meets European fire safety standards for exposure to different ignition sources, namely a lit cigarette and butane flame. Assessment of the ignitability of upholstered furniture